



FAT *Pipe*

SD-WAN

DATASHEET

FatPipe Networks

3rd Floor, Ragula Tech Park, Type II/16, Dr. VSI Estate (Phase 1), Thiruvanniyur, Chennai - 600 041 India
www.fatpipeinc.com • info@fatpipeinc.com • Tel: +91 44 6670 7200

FatPipe SD-WAN Solution:



- Seamless session failover in sub-seconds for session continuity using our patented technology. Ensuring clear and superior VoIP and video traffic.
- Granular data/session prioritization over multiple carrier lines.
- Selective encryption across the overlay fabric, not “double encryption” (which impedes session performance). FatPipe holds a patent on this technology.
- FatPipe architecture ensures that even if a remote Orchestrator is unavailable due to outages, the local boxes will continue to operate and transmit data efficiently.
- FatPipe load balances on Layer 3, and is compatible and future proofed for IoT, Layer 2 fabric, etc.
- Single pane of glass management.

SD-WAN for HQ/Branch Site Redundancy & Load Balancing:

- **Deploy FatPipe SD-WAN solution** into network, to pass traffic on all available links.
- **Load Balance traffic** on all available paths and Automatic Failover to additional lines, in case of link failure, ensures uninterrupted service availability. All lines in active/active state.
- **Internet circuits at HQ and all sites with FatPipe appliances can now be used as failover for DIA circuits**, with secure transmission over public connections, with FatPipe patented MPsec encryption.
- **Provide for fast turn on of branch connectivity to main site/DCs**, using whatever Internet circuits are available (DIA, MPLS, Ethernet, broadband, cable, wireless, microwave, satellite, etc.).
- **Enable Orchestrator with Central Policy Propagation** to centrally control WANs and easily manage branches and branch deployments.
- **Branch appliances “phone home” for auto configurations** and policy-based routing rules.
- **Zero downtime is assured** as long as one link at the site is up and running.
- **IPSec tunnels terminate at the appliance for VPN functionality.**
- **Active link monitoring** for available bandwidth, latency, jitter and packet loss allows FatPipe to send traffic on the best path with better characteristics.
- **Prioritize outbound sessions** with FatPipe policy-based routing, ensuring high priority sessions have the required bandwidth.
- **Granular control of VoIP, Video, Skype, Lync, etc.** –with multiple options to define an application. (Source/Destination IP, ADS user, Source/Destination Port, Protocol, Pre-classified DSCP markers.)
- **Fail-to-Wire configuration**, in highly unlikely event of component/unit failure. Optional HA Paired units.

Multi-Line WAN Aggregation:

- **Sub-Second Stateful VoIP Failover.** Patented technology fails VoIP traffic over in a sub second without dropping the call. With FatPipe, VoIP and other traffic are sent over ONE line only, and if that line fails, the data automatically fails over to another other line instantly. (Other vendors will send the same VoIP traffic over two lines, and whichever data reaches first is selected. Duplicating VoIP traffic causes clogging and inefficient traffic flow for offices that handle multiples of calls being placed simultaneously, or PBX and cloud services.)
- **Stateful Sub-Second Session Failover.** Patented technology works similarly for all data traffic and is especially valuable for companies that use Oracle and SAP. FatPipe automatically fails over all data sessions without dropping them when a line fails. This is important when production monitoring data is transmitted live. If a line fails in the middle of a transaction, the transaction is failed over without causing a loss of data.
- **True Outbound Load Balancing**, rather than just placing data session on two lines. Maximizes the data traffic and speeds up data transmission resulting in better ROI.
- **Rotating IP address Support**, Usually ISP lines with rotating/dynamic IP addresses are less expensive, and so small branches may be able to use them cost effectively.
- **Multiple Orchestrator Options**, can be in-band (on the customer’s networks for security), Hosted (data center outside the customer’s network), or Cloud Hosted as a service. Depending on the customer security requirements.
- **Built-in Firewall** appliance to be a single box solution.
- **No Data Plane Backhaul**, data does not have to leave the network if desired/required.
- **Threshold-Based Session Failover**, - based upon variable parameters (latency, jitter, packet loss) that you apply and set for specific applications (VoIP, Skype, Salesforce, O365, e.g.) to ensure the session follows the best path for that application.

Visibility

- FatPipe WAN visibility, management and Reporting with Enterprise Dashboard View.

Deployment

- Pre-deployment meetings, whiteboard sessions, and Visio diagrams to outline complete installation, deployment, and support.
- Collaborated efforts on staging, infrastructure configuration, testing, turn up and installations.

Delivery Timelines

- Unit delivery: International shipping delivery timetables apply
- Installation: One-week turnaround.

FatPipe SD-WAN Feature Matrix

Features	Standard	Real-Time	Enterprise
Outbound Load Balancing	✓	✓	✓
QoS	✓	✓	✓
IPSec VPN	✓	✓	✓
MPSec	✓	✓	✓
Sub-Second Failover	✓	✓	✓
Site-to-Site Overlay	✓	✓	✓
Split Tunneling / Local Internet Breakout	✓	✓	✓
Auto Config	✓	✓	✓
Firewall	✓	✓	✓
IPS, Geo Blocking	✓	✓	✓
Rotating IP Support	✓	✓	✓
Web Filter		✓	✓
Threshold Based Failover		✓	✓
Selective Encryption		✓	✓
Layer 3 Routing		✓	✓
Routing Protocol Support		✓	✓
Layer 7 PRR			✓
Full Mesh VPN			✓
Advanced VLAN Support			✓
L2 Routing			✓
Multicast Support			✓
Double NAT Support			✓
Advanced Routing – BGP, OSPF			✓
WAN Optimization Add-on license required			✓
Antivirus Add-on license required			✓
IDS Add-on license required			✓

Hardware Specifications	
Hardware	STD-SFF
Rack-Mountable	1U
Operating System	64 Bit
Single Power Supply (Watts)	AC (110V/220V) DC (12V/5A) 60W Max
RAM	8 GB
CPU	Intel Celeron 3855u 1.6GHz Dual Core with AESNI or Equivalent
Data Storage (SSD)	256 GB
Included Ports	4
Optional Ports	N/A
Max. Ports	6 (6 Port Gbe Onboard)
Expansion Slots	0
HW Dimensions (L x W x H)	13" x 19" x 1.75"
Shipping Dimensions (L x W x H)	21" x 15" x 6"
Shipping Weight	10 lbs
Operating Temperature	10 - 35 deg C
Non - Operating Temperature	40 - 70 deg C
Mounting Rail Kit	Yes
Maximum WAN Throughput	300 Mbps
USB ports	2



FatPipe Networks

3rd Floor, Ragula Tech Park, Type II/16, Dr. VSI Estate (Phase 1), Thiruvanniyur, Chennai - 600 041
India • www.fatpipe.com • Info@fatpipeinc.com • Tel: +91 44 6670 7200

FatPipe Networks™, MPVPN®, MPSec™, Datacenter-to-Branch®, Datacenter-to-Device®, and FatPipe Symphony™ are trademarks or registered trademarks of FatPipe Networks and other countries. All other product names mentioned herein are trademarks of their respective owners. © FatPipe Networks

FatPipe owns US Patent Numbers: 6,253,247; 6,295,276; 6,493,341; 6,775,235; 7,269,143; 7,406,048; 7,444,506; 7,877,510; 8,356,346; 8,780,811; & 8,995,252.